

Fittings / Downlights

7W Firestay LED CCT Downlight - Dimmable, 3 Way CCT, 40°, Tool Free



The Firestay LED CCT 3 way colour switch downlight is one of our flagship products. Colour selectable as standard with a 7 year guarantee, the Firestay LED CCT downlight is a market leader when it comes to downlights. The front facing switch enables the user to seamlessly change the colour temperature to suit the mood of any space.

- Firestay Certification: 30, 60 and 90 minute solid joist ceilings, 30 minute I-Joist & Metal Web ceiling systems
- 6 in 1 Fixture, 3 colour temperatures, 2 bezels
- Includes satin & white magnetic bezels
- Front CCT switch
- IC rated

Technical Specification

| | |
|---------------------|-------|
| Product Code | 10510 |
|---------------------|-------|

Reference

| | |
|------------------|---------|
| Guarantee | 7 Years |
|------------------|---------|

| | |
|------------|---------------|
| EAN | 5013588105109 |
|------------|---------------|

| | |
|-----------------------|----------|
| Commodity Code | 94054099 |
|-----------------------|----------|

| | |
|--------------------------|----|
| Country Of Origin | CN |
|--------------------------|----|

| | |
|--------------------|----------|
| UNSPSC Code | 39111515 |
|--------------------|----------|

Technical Specification

| | |
|--------------------------------|----------------|
| Volts (V) | 220-240 |
| Watts (W) | 7 |
| Colour Temp (K) | 3000/4000/6000 |
| Dimmable? | 1 |
| Lumens (lm) | 550-600 |
| Candelas (cd) | 660 |
| Life Hours | 50,000 |
| Beam Angle | 40° |
| CRI (Ra) | 85 |
| Switching Cycles | 10,000 |
| Frequency (Hz) | 50/60 |
| Energy Consumption (kWh/1000h) | 7 |
| IP Rating | IP65 |

Dimensions

| | |
|------------------------|----|
| Width (mm) | 63 |
| Depth (mm) | 72 |
| Diameter (mm) | 82 |
| Downlight Cut Out (mm) | 65 |

Packaging Information

| | |
|---------------------------|---------|
| Single Carton Height (mm) | 9 |
| Single Carton Width (mm) | 9.7 |
| Single Carton Depth (mm) | 9.7 |
| Single Carton Weight (KG) | 0.321 |
| Individual Volume | 0.00085 |
| Inner Box Qty | 10 |
| Inner Box Height (mm) | 51 |
| Inner Box Width (mm) | 21 |
| Inner Box Depth (mm) | 11 |
| Inner Box Weight (kg) | 3.6 |
| Outer Box Qty | 20 |
| Outer Box Height (mm) | 52.5 |
| Outer Box Width (mm) | 22.5 |
| Outer Box Depth (mm) | 23.5 |
| Outer Box CMB | 0.02776 |